

## FEATURES & BENEFITS

### PROMOTES NATURAL GAIT

- Accommodates crossover gait and side-to-side movement on the treadmill
- Eliminates the tendency for people to widen their stance and alter their gait as is the case with a side-to-side split belt\*
- Synchronized belt speeds and a minimal gap for a smooth transition between belts

### USB DIGITAL INTEGRATION

- Straightforward USB integration with all leading motion capture software
- Smart platform technology simplifies the user experience

### OPTIMIZED FOR BIOMECHANICAL APPLICATIONS

- Optional StrideWorks software resolves front/rear forces into left/right forces which can be streamed in real-time into all leading motion capture software
- Two 6-axis force platforms (8900N capacity) provide independent forces for each limb even during double-support gait phases
- Bidirectional belt speed up to 12 mph
- Removable handrails for maximum visibility of motion capture markers

### ENHANCED MECHANICAL PERFORMANCE

- A high frequency structure for reliable data during walking and running
- Long-life bearing system
- Responsive tracking system for consistent and reliable performance

\*Altman, et al., Gait Posture. 2012 Feb; 35(2): 287-291.

## SPECIFICATIONS

Integrated Force Plate Specifications	
Vertical Force Plate Capacity	8900 N
Horizontal Force Plate Capacity	4500 N
Installed Force Platform Resonant Frequency	300 Hz (Fx, Fy)
Linearity	±0.2 % full scale output
Hysteresis	±0.2 % full scale output
Treadmill Specifications	
Maximum Speed (Bidirectional)	19.3 km/h (12 mph)
Structural Resonance Frequency	120 Hz
Working Surface of Each Belt	75 (L) x 61 (W) cm
Total Working Surface	150 (L) x 61 (W) cm
Deck Height	30 cm
Overall Dimensions (Including Handrails)	203 (L) x 112 (W) x 125 (H) cm
Side & Horizontal Front Handrails	Removable
Vertical Front Handrail Supports (Removable on non-incline model)	Two posts, 91 cm high and 91 cm apart
Weight	400 kg
Maximum treadmill inclination (Optional)	25% grade (14 degrees)
Power Requirements	
208 VAC, 3-phase, wye-connected, 20-Amp service, 50/60Hz*	
Available StrideWorks Software	
Main Functionality	Convert front/rear forces into left/right forces
Integration	Stream real-time left/right forces into MoCap software

\*For other power availability, please contact AMTI



[www.amti.biz](http://www.amti.biz)

CE ISO 9001 certified

©2024 Specifications subject to change without notice.  
MOBIUS Treadmill Brochure-rev2

176 Waltham Street, Watertown, MA 02472 USA  
+1-617-926-6700 | [sales@amtmail.com](mailto:sales@amtmail.com) | [www.amti.biz](http://www.amti.biz)

# MOBIUS TREADMILL



[www.amti.biz](http://www.amti.biz)




25% grade incline option available



Removable Handrails



Dual Wear-Resistant Belts



Front/Rear Belts Promote Natural Gait



High-Frequency Structure

1103115